

ICS % "\$(\$" &\$
77G N &)

DB36

DB36#H %' - &\$&(

DB36

Stationary pollution source exhaust gas, Technical requirements for acceptance and operation of county

| | | |
|-------|-----------|--------|
| | | |
| 1 | | 1 |
| 2 | | 1 |
| 3 | | 1 |
| 4 | | 2 |
| 5 | | 3 |
| A | NMHC-CEMS |4 |

86' *#H %' -—&\$&(

GB/T 1. 1- 2020

1

中国标准出版社

%

&

GB/T 3836.1
GB/T 4208
GB/T 16157
GB 50057
GB 50093

1
I P

86' *#H %' -—&\$&{(

FID

' " (

Vcbh] bi ci g acb] hcf] b[gmghYa fi7AGL

CMS

(

(" %

(" % %

(" % & NMHC-CEMS

(" &

(" & %

(" & % % NMHC-CEMS

HJ 1286 HJ 1013

(" & % & NMHC-CEMS

3

(" & &

(" & & %NMHC-CEMS

HJ 1286

(" & & &

2000kg/

("' " NMHC-CEMS

(" (NMHC-CEMS

HJ 1286

(")

(")" %

9

NMHC-CEMS

(")" &

HJ 38

FID

FID

HJ 1012

GC-FID

-FID

(")" '

CMS

HJ 75

(" *

HJ 75 HJ 212

)

)" % NMHC-CEMS

HJ 75 HJ 1286

)" &

)" ' NMHC-CEMS

48h

4

6h

)" (NMHC-CEMS

4

6h

)") NMHC-CEMS

)" * NMHC-CEMS

5

3

86' *#H %' -—&\$&(

5" &

CEMS

CEMS

CEMS

CEMS

GB/T 4208 IP50 S

86' *#H %' -—&\$&{

5" &

10%

10%

86' *#H %' -—&\$&(

5''

CEMS

70m

15 30 85%

NMHC-CA*,

86' * #H % ' - —&\$\$(

5" (

CEMS

2 10A

2m

2m

1m

1.2m

2m

Z

0.9m

20m

CEMS

4m

4m

CEMS

GB/T 16157

80mm

90mm

CEMS

e

86' *#H %' -—&\$&{(

5" (

CEMS

GB 50093 GB 50168

PVC

24h

GB 4208

IP24

IP54

4 mm²

4

GB 50057

1 m

0.3 m

α>|